



Rounded hoods available in white, ivory, beige, and bronze



Hood Front



Hood back

Recessed track system can be installed as surface mount with round hood. Track holes can be covered with angle or hole caps.

Hoods are sold in two sections—front and back

Hood length cut to size;

Maximum length of 21ft (6.4m)

NOTE: Custom hoods available in any size and shape

Extruded, Rounded Hood		
Size	(A) Front Section Item #	(B) Back Section Item #
5 1/2" / 140mm	SM10F-5.5	SM02B-5.5

	MaestroShield Rounded Hood	Bent Hood
Wall Thickness	1.5mm (66% thicker than bent)	0.9mm
Packing	Stacks for easier and more secure packing	Does not stack; difficult to pack
Shipping	Cheaper and less damage in handling	More expensive with frequent damage
Inventory	Less needed due to common pieces	No common pieces requires more inventory
Powder Coat Warranty	10-year warranty on powder coating (1-year in coastal regions within 1 mile of saltwater coastline)	1-year

Impact-Rated Side Caps		
Size	Weight	Item #
5 1/2"	.75 lbs	CA10-139

Side Caps available in white, ivory, beige, and bronze



Internal stainless steel inserts for easy installation of motor plates for an external smooth appearance

	MaestroShield Side Cap	Universal Side Cap
Thickness of Casting	6mm	3.2mm
Threaded Inserts for Motor Plates	Threaded Galvanized Steel Insert - 6.85mm deep	Threaded Aluminum - 3mm deep (some not threaded)
Powder Coat Warranty	10-year	1-year
Openings for Manual Crank	Yes - in all three positions	Not in all positions (requires drilling)
Recessed Hood for flush appearance	Yes	No

